

Attachment to CLIA Standard

CRUISE INDUSTRY WASTE MANAGEMENT PRACTICES AND PROCEDURES

REVISED: (November 27, 2006)

The cruise industry is dedicated to preserving the marine environment and oceans upon which our ships sail. As a stated industry standard, CLIA members have adopted aggressive programs of waste minimization, waste reuse and recycling, and waste stream management set forth in the following. In addition, CLIA members are working in a number of areas to identify and implement new technologies in order to improve the environmental performance of their ships. CLIA member lines currently have agreed to utilize waste management practices and procedures, which meet or exceed the stringent standards as set forth in international treaties and applicable U.S. laws.

Introduction

The cruise industry is inextricably linked to the environment. Our business is to bring people to interesting places in the world, over the water. Recognizing the future of the industry depends on a clean and healthy environment; cruise industry senior management is committed to stewardship of the environment and establishing industry practices that will make CLIA member cruise ship operators leaders in environmental performance.

This document outlining member line practices has been developed under the auspice of the industry's professional organizations, the Cruise Lines International Association (CLIA), the Florida Caribbean Cruise Association (FCCA), and the Northwest Cruise Ship Association (NWCA). The purpose of this document is to set forth cruise industry waste management practices and procedures that CLIA member cruise vessel operators have agreed to incorporate into their respective Safety Management Systems.

In the development of industry practices and procedures for waste management, the members of the Cruise Lines International Association have endorsed policies and practices based upon the following fundamental principles:

- Full compliance with applicable laws and regulations;
- Maintaining cooperative relationships with the regulatory community;
- Designing, constructing and operating vessels, so as to minimize their impact on the environment;
- Embracing new technology;
- Conserving resources through purchasing strategies and product management;
- Minimizing waste generated and maximize reuse and recycling;
- Optimizing energy efficiency through conservation and management;
- Managing water discharges; and
- Educating staff, guests and the community.

Discussion

Just as on shore, ship operations and passengers generate waste as part of many daily activities. On ships, waste is generated while underway and in port. Because ships move, the management of these wastes becomes more complicated than for land-based activities, as the facilities and laws change with the location of the ship. Facilities on the ships as well as management practices must be designed to take into account environmental laws and regulations around the world and the various local and state laws and regulations. Moreover, because waste management ultimately becomes a local activity, the local port infrastructure, service providers, and local waste disposal vendors are factors in the decision-making processes.

On an international level, environmental processes are an important part of the International Maritime Organization's (IMO's) policies and procedures for the maritime industry. CLIA member lines have agreed to incorporate environmental performance into Safety Management Systems (SMS) and MARPOL mandated Waste Management Manuals. Under agreements and laws specific to many nations, these programs are routinely reviewed by Port States to ensure compliance. For example, in the United States, the US Coast Guard has jurisdiction over environmental matters in ports and waterways and conducts passenger ship examinations that include review of environmental systems, SMS documentation and such MARPOL-mandated documents as the Oil Record Book and the Garbage Record Book. Within the United States, environmental laws and regulations apply include the Clean Water Act, the Refuse Disposal Act, the Resource Conservation and Recovery Act, The Clean Air Act, the Oil Pollution Act of 1990, and the Pollution Prevention Act, to name a few, which apply to all ships within U.S. waters.

The industry effort to develop waste management practices and procedures has focused on the traditional high volume wastes (garbage, graywater, blackwater, oily residues (sludge oil) and bilge water), pollution prevention, and the small quantities of hazardous waste produced onboard. In the process, CLIA members have shared waste management strategies and technologies, while focusing on a common goal of waste reduction.

The process of waste reduction includes waste prevention, the purchasing of products that have recycled content or produce less waste (e.g. source reduction), incineration, and recycling or reuse of wastes that are generated. The ultimate goal is to have the waste management culture absorbed into every facet of cruise vessel operation. A fully integrated system beginning with the design of the vessel should address environmental issues at every step.

Management practices for waste reduction should start before a product is selected. Eco-purchasing and packaging are vital to the success of any environmental program, as are strategies to change packaging, processes and management to optimize the resources used.

The commitment of the industry to this cooperative effort has been quite successful, as companies have shared information and strategies.

Industry Standard Waste Handling Procedures

CLIA member lines have agreed that hazardous wastes and waste streams onboard cruise vessels will be identified and segregated for individual handling and management in accordance with appropriate laws and regulations. They have further agreed, hazardous wastes will not be discharged overboard, nor be commingled or mixed with other waste streams.

- A. **Hazardous Waste Collection and Storage onboard Ship:** *CLIA member lines have agreed that specific procedures for hazardous waste collection, storage and crew training will be addressed in each ship's SMS or equivalent onboard instruction in the Case of US registry vessels.*
- B. **Photo Processing, Including X-Ray Development Fluid Waste:** *CLIA member lines have agreed to eliminate the discharge of silver from these sources into the marine environment through the use of best available technology that will reduce the silver content of the waste stream below levels specified by prevailing regulations or by treating all photo processing and x-ray development fluid waste (treated or untreated) as a hazardous waste and landing ashore in accordance with RCRA requirements.*

There are several waste streams associated with photo processing operations that have the potential to be regulated under the Resource Conservation and Recovery Act (RCRA). These waste streams include spent fixer, spent cartridges, expired film and silver flake.

Photographic fixer removes the unexposed silver compounds from the film during the developing process. The spent fixer can have as much as 2000-3000 parts per million (ppm) of silver. Silver bearing waste is regulated by RCRA as a hazardous waste if the level of silver exceeds 5 ppm as determined by the Toxicity Characteristic Leaching Procedure (TCLP) test.

Silver recovery units may be used to reclaim the silver from the used fixer waste stream. There are two types of recovery units. These are active (with electricity) and passive (without electricity) units. The active unit uses electricity to plate silver onto an electrode. The passive unit uses a chemical reaction between steel wool and silver to remove most of the silver from solution. Utilizing the best available technology, the equipment currently onboard CLIA member cruise ships is conservatively estimated to reduce the silver content of this effluent below 4 mg/l (milligrams/l or ppm)

Handling Method 1 Employed by Member Lines:

Treat used photographic and x-ray development fluids to remove silver for recycling.

Verify that the effluent from the recovery unit is less than 5 parts per million (ppm) silver, as measured by EPA-approved methodology.

After treatment, the residual waste stream fluid is non-hazardous and landed ashore as industrial waste.

Handling Method 2 Employed by Member Lines:

Used photographic and x-ray development fluids, either treated or untreated, may be assumed to be a hazardous waste. In this event, they are landed ashore in accordance with the requirements of the Resource Conservation and Recovery Act (RCRA).

- C. **Dry-cleaning waste fluids and contaminated materials:** *CLIA member lines have agreed to prevent the discharge of chlorinated dry-cleaning fluids, sludge, contaminated filter materials and other dry-cleaning waste byproducts into the environment.*

Shipboard dry cleaning facilities use a chlorinated solvent called perchlorethylene (also known as PERC or tetrachloroethylene) as a dry cleaning fluid. This is the approved dry cleaning solvent for these units. Operators must receive specific required training for the correct use of this chemical and its associated precautions. This solvent should be used in accordance with all safety procedures including appropriate personal protective equipment (PPE).

The dry cleaning units produce a small volume waste from condensate, the bottoms of the internal recovery stills, waste products from button and lint traps, spent perchloroethylene and filter media. This waste is comprised of dirt, oils, filters material, and spent solvent. Each ship utilizing these dry-cleaning units produces approximately two pounds of waste material weekly. However, the amounts may vary greatly by season and passenger load. This material is classified as hazardous waste under RCRA and must be disposed of accordingly.

Handling Method 1 Employed by Member Lines:

Perchloroethylene (PERC) and other chlorinated dry-cleaning fluids, contaminated sludge and filter materials are hazardous waste and landed ashore in accordance with the requirements of RCRA.

- C. **Print Shop Waste Fluids:** *CLIA member lines have agreed to prevent the discharge of hazardous wastes from printing materials (inks) and cleaning chemicals into the environment.*

Print shop waste may contain hazardous waste. Printing solvents, inks and cleaners all may contain hydrocarbons, chlorinated hydrocarbons, and heavy metals that can be harmful to human and aquatic species. Recent advances in printing technology and substitution of chemicals that are less hazardous reduces the volume of print shop waste generated and reduces the impact of these waste products.

CLIA member lines have agreed to utilize, whenever possible, printing methods and printing process chemicals that produce both less volume of waste and less hazardous waste products, that shipboard printers will be trained in ways to minimize printing waste generated, and that alternative printing inks such as soy based, non-chlorinated hydrocarbon based ink products will be used whenever possible. The member lines have further agreed that all print shop waste including waste solvents, cleaners, and cleaning cloths will be treated as hazardous waste, if such waste contains chemical components that may be considered as hazardous by regulatory definitions, and that all other waste may be treated as non-hazardous.

Handling Method 1 Employed by Member Lines:

When using traditional or non-soy based inks and chlorinated solvents, all print shop waste is treated as hazardous, and discharged ashore in accordance with RCRA.

Handling Method 2 Employed by Member Lines:

Shipboard printing processes use non-toxic based printing ink such as soy based, non-chlorinated solvents, and other non-hazardous products to eliminate hazardous waste products.

- D. Photo Copying and Laser Printer Cartridges:** *CLIA member lines have agreed to initiate procedures so as to maximize the return of photocopying and laser printer cartridges for recycling, and in any event, have agreed that these cartridges will be landed ashore.*

Increased use of laser and photo copying equipment on shore as well as onboard ship results in the generation of increased volumes of waste cartridges, inks, and toner materials. CLIA member lines have agreed to use only such inks, toners and printing/copying cartridges that contain non-hazardous chemical components, and that none of these cartridges or their components should be disposed of by discharge into the marine environment. In recognition of the member lines' goal of waste minimization, they have further agreed these cartridges should, whenever possible, be returned to the manufacturer for credit, recycling, or for refilling.

Handling Method Employed by Member Lines:

CLIA member lines have agreed that wherever possible, photo copying and laser printer cartridges will be collected, packaged and returned for recycling and when this is not possible, that these materials will not be discharged into the sea or other bodies of water but will be handled as other shipboard waste that is landed ashore for further disposal.

- F. Unused And Outdated Pharmaceuticals:** *CLIA member lines have agreed to ensure that unused and/or outdated pharmaceuticals are effectively and safely disposed in accordance with legal and environmental requirements.*

In general ships carry varying amounts of pharmaceuticals. The pharmaceuticals carried range from over-the-counter products such as anti-fungal creams to prescription drugs such as epinephrine. Each ship stocks an inventory based on its itinerary and the demographics of its passenger base. CLIA member lines have agreed that all pharmaceuticals will be managed to ensure that their efficacy is optimized and that disposal is done in an environmentally responsible manner.

CLIA member lines have further agreed that when disposing of pharmaceuticals, the method used will be consistent with established procedures, and that pharmaceuticals and medications which are off specification or which have exceeded their shelf-life, and stocks that are unused and out of date, cannot be used for patients and therefore will be removed from the ship. Further, each regulatory jurisdiction has a posting of listed pharmaceuticals that must be considered hazardous waste once the date has expired or the item is no longer considered good for patient use.

Through onboard management of the medical facility, CLIA member lines have agreed that stocks of such listed pharmaceuticals are returned to the vendor prior to date of expiration. Pharmaceuticals that are being returned and which have not reached their expiration date are shipped using ordinary practices for new products.

Safety and Health

CLIA member lines have agreed that all expired listed pharmaceuticals will be handled in accordance with established procedures and all personnel handling this waste will receive

appropriate training in the handling of hazardous materials. As guidance, the US Environmental Protection Agency (EPA) has issued a report that clarifies the fact that residuals, such as epinephrine, found in syringes after injections are not considered an acutely hazardous waste by definition and may be disposed of appropriately in sharps containers. Member lines have agreed that all Universal Precautions will be adhered to when handling sharps.

Handling Method 1 Employed by Member Lines:

Establish a reverse distribution system for returning unexpired, unopened non-narcotic pharmaceuticals to the original vendor.

Handling Method 2 Employed by Member Lines:

Appropriately destroy narcotic pharmaceuticals onboard ship in a manner that is witnessed and recorded.

Handling Method 3 Employed by Member Lines:

Land listed pharmaceuticals in accordance with local regulations. Listed pharmaceuticals are a hazardous waste having chemical compositions which prevent them from being incinerated or disposed of through the ship's sewer system. Listing of such pharmaceuticals may vary from state to state.

Handling Method 4 Employed by Member Lines:

Dispose of other non-narcotic and non-listed pharmaceuticals through onboard incineration or landing ashore.

- G. Fluorescent and Mercury Vapor Lamp Bulbs:** *CLIA member lines have agreed to prevent the release of mercury into the environment from spent fluorescent and mercury vapor lamps by assuring proper recycling or by using other acceptable disposal methods.*

Fluorescent and Mercury Vapor lamps contain small amounts of mercury that could potentially be harmful to human health and the environment. To prevent human exposure and contamination of the environment, CLIA member lines have agreed that these lamps will be handled in an environmentally safe manner. Recycling of mercury from lamps and other mercury containing devices is the preferred handling method and is encouraged by various states. The recycling of fluorescent lamps and high intensity discharge (HID) lamps keeps potentially hazardous materials out of landfills, saves landfill space and reduces raw materials production needs.

The recycling of fluorescent and HID lamps is a proven technology capable of reliably recovering greater than 99 percent of the mercury in the spent lights. At the recycling facility, this is done by using a crush-and-sieve method. In this process, the spent tubes are first crushed and then sieved to separate the large particles from the mercury containing phosphor powder. The phosphor powder is collected and processed under intense heat and negative pressure, a process called retorting. The mercury is volatilized and then recovered by condensation. The glass particles are segregated and recycled into other products such as fiberglass. Aluminum components are also recycled separately.

Storage and handling of used lamp bulbs pose no compatibility problems. Disposal of the glass tubes can be accomplished by (1) processing with shipboard lamp crusher units that filter and adsorb the mercury vapor through H.E.P.A. and activated carbon or (2) by keeping the glass tubes intact for recycling ashore. The intact lamps or crushed bulbs are classified as “Universal Waste” when they are shipped to a properly permitted recycling facility; as such, testing is not required. The filters are disposed of as a hazardous waste in accordance with applicable US EPA or other prevailing laws and regulations.

Handling Method Employed by Member Lines:

- (1) Fluorescent and mercury vapor lamps are collected and processed aboard by lamp crusher units and disposed of as stated above; or
- (2) Fluorescent and mercury vapor lamps are collected intact and landed for recycling or disposal in accordance with prevailing laws and regulations.

H. Other Mercury Containing Products: *CLIA Member lines have agreed to prevent the discharge of mercury containing products into the sea.*

Reduction in use: Where feasible, CLIA members will reduce the use of mercury containing products.

Disposal: Once mercury-containing products are no longer able to be used, or require disposal, these products shall be landed ashore as universal or hazardous waste as appropriate.

I. Batteries: *CLIA member lines have agreed to prevent the discharge of spent batteries into the marine environment.*

If not properly disposed of, spent batteries may constitute a hazardous waste stream. Most of the large batteries are on tenders and standby generators. Small batteries used in flashlights and other equipment and by passengers, account for the rest. There are four basic types of batteries used.

Lead-acid batteries – These are used in tenders and standby generators. They are wet, rechargeable, and usually six-celled. They contain a sponge lead anode, lead dioxide cathode, and sulfuric acid electrolyte. The electrolyte is corrosive. These batteries require disposal as a hazardous waste, unless recycled or reclaimed.

Lead-acid batteries use sulfuric acid as an electrolyte. Battery acid is extremely corrosive, reactive and dangerous. Damaged batteries will be drained into an acid-proof container. A damaged and leaking battery is then placed in another acid-proof container, and both the electrolyte and the damaged battery placed in secure storage for proper disposal as a hazardous waste.

Nickel-cadmium (NiCad) batteries – These are usually rechargeable, and contain wet or dry potassium hydroxide as electrolyte. The potassium hydroxide is corrosive and the cadmium is a characteristic hazardous waste. Therefore, NiCad batteries will be disposed of as hazardous waste, unless recycled or reclaimed.

Lithium batteries – These are used as a power source for flashlights and portable electronic equipment. All lithium batteries will be disposed of as hazardous waste, or sent out for reclamation.

Alkaline batteries – These are common flashlight batteries and are also used in many camera flash attachments, cassette recorders, etc. They should be recycled, properly disposed or reclaimed.

Handling Method Employed by Member Lines:

Spent batteries are collected and returned for recycling and/or disposal in accordance with prevailing regulations. Discarded batteries are isolated from the refuse waste stream to prevent potentially toxic materials from inappropriate disposal. The wet-cell battery-recycling program is kept separate from the dry battery collection process. Intact wet-cell batteries are sent back to the supplier. Dry-cell batteries are manifested to a licensed firm for recycling.

- J. Bilge and Oily Water Residues:** *CLIA member lines have agreed to meet or exceed the international requirements for removing oil from bilge and wastewater prior to discharge.*

The area of the ship at the very bottom of the hull is known as the bilge. The bilge is the area where water collects from various operational sources such as water lubricated shaft seals, propulsion system cooling, evaporators, and other machinery. All engine and machinery spaces also collect oil that leaks from machinery fittings and engine maintenance activities. In order to maintain ship stability and eliminate potential hazardous conditions from oil vapors in engine and machinery spaces, the bilge spaces should be periodically pumped dry. In discharging bilge and oily water residues, both international regulations (MARPOL) and United States regulations require that the oil content of the discharged effluent be less than 15 parts per million and that it not leave a visible sheen on the surface of the water.

All ships are required to have equipment installed onboard that limits the discharge of oil into the oceans to 15 parts per million when a ship is en route and provided the ship is not in a special area where all discharge of oil is prohibited. Regulations also require that all oil or oil residues, which cannot be discharged in compliance with these regulations, be retained onboard or discharged to a reception facility. The equipment and processes implemented onboard cruise ships to comply with these requirements are complex and sophisticated.

The term “*en route*” as utilized in MARPOL (73/78) Regulation 9(b) is taken to mean while the vessel is underway. The U.S. Coast Guard has informed CLIA that it agrees with this meaning of “*en route*.”

In accordance with MARPOL (73/78) Regulation 20 and as appropriate, US regulations (33CFR151.25), CLIA member lines have agreed that every cruise ship of 400 gross tons and above shall be provided with an oil record book which shall be completed on each occasion whenever any of numerous specified operations take place in the ship and that operations include:

- a. Ballasting or cleaning of fuel oil tanks,
- b. Discharge of dirty ballast or cleaning water from the fuel oil tanks above,
- c. Disposal of oily residues,
- d. And discharge of bilge water that accumulated in machinery spaces.

Requirements regarding the keeping of an Oil Record Book as well as the form of the Oil Record Book are also found in MARPOL and in U.S. Coast Guard regulations (33CFR151).

Handling Method Employed by Member Lines:

Bilge and oily water residue are processed prior to discharge to remove oil residues, such that oil content of the effluent is less than 15 ppm as specified by MARPOL Annex 1.

- K. Glass, Cardboard, Aluminum and Steel Cans:** *CLIA member lines have agreed to eliminate, to the maximum extent possible, the disposal of MARPOL Annex V wastes into the marine environment. This will be accomplished through improved reuse and recycling opportunities. They have further agreed that no waste will be discharged into the marine environment unless it has been properly processed and can be discharged in accordance with MARPOL and other prevailing requirements.*

Management of shipboard generated waste is a challenging issue for all ships at sea. This is true for cruise vessels, other commercial vessels, military ships, fishing vessels and recreational boats. Waste products in the past were made from natural materials and were mostly biodegradable. Today's packaging of food and other products present new challenges for waste management. A large cruise ship today can carry over three thousand passengers and crew. Each day, an average cruise passenger will generate two pounds of dry trash and dispose of two bottles and two cans.

A strategy of source reduction, waste minimization and recycling has allowed the cruise industry to significantly reduce shipboard generated waste. To attain this, CLIA member lines have agreed to adopt a multifaceted strategy that begins with waste minimization to decrease waste from provisions brought onboard. This means purchasing in bulk, encouraging suppliers to utilize more efficient packaging, reusable packaging, and packaging materials that are more environmentally friendly—those that can be more easily disposed of or recycled. In fact, through this comprehensive strategy of source reduction, total waste on passenger vessels has been reduced by nearly half over the past ten years.

Another important component of the industry's waste reduction strategy is product or packaging recycling. Glass, aluminum, other metals, paper, wood and cardboard are, in most cases, recycled. Wood and cardboard may be incinerated when appropriate.

Handling Method Employed by Member Lines:

MARPOL Annex V ship waste is minimized through purchasing practices, reuse and recycling programs, landing ashore and onboard incineration in approved shipboard incinerators. Any Annex V waste that is discharged at sea will be done in strict accordance with MARPOL and any other prevailing requirements.

- L. Incinerator Ash:** *CLIA member lines have agreed to reduce the production of incinerator ash by minimizing the generation of waste and maximizing recycling opportunities, and that the discharge of incinerator ash containing hazardous components will be prevented through a program of waste segregation and periodic ash testing.*

Incinerator ash is not normally a hazardous waste. Through relatively straightforward waste management strategies, items that would cause the ash to be hazardous are separated from the waste stream and handled according to accepted hazardous waste protocols. In general, source segregation for waste streams is foundational for onboard waste management and is incorporated into the waste management manual required by MARPOL. Waste management for onboard waste streams include the following: source reduction, minimization, recycling, collection, processing and discharge ashore. This allows the incinerator to be used primarily for food waste, contaminated cardboard, some plastics, trash and wood.

Member lines have agreed that incinerator ash will be tested at least once quarterly for the first year of operation to establish a baseline and that testing may then be conducted once a year. The member lines have further agreed that a recognized test procedure will be used to demonstrate that ash is not a hazardous waste. A recognized test procedure includes the following metals as indicators for toxicity - arsenic, barium, cadmium, chromium, lead, mercury, selenium, and silver. Special attention is placed on the removal of batteries from the incinerator waste stream. The use of incinerators saves landfill space and prevents the build up of material onboard that could become the breeding ground for insects, rodents and other vermin.

Handling Method Employed by Member Lines:

Proper hazardous waste management procedures are to be instituted onboard each ship to assure that waste products, which will result in a hazardous ash, are not introduced into the incinerator. Non-hazardous incinerator ash may be disposed of at sea in accordance with MARPOL Annex V. Ash identified as being hazardous is disposed of ashore in accordance with RCRA.

M. Wastewater reclamation

Because of the amounts of fresh water involved, and its restricted availability onboard ship (all fresh water must be either purchased or generated onboard), fresh water is a valuable commodity. Therefore, water management is extremely important and takes the form of both minimizing water usage and the potential reclamation and reuse of water for non-potable purposes. Many CLIA companies are researching new technology and piloting graywater treatment systems onboard their vessels. CLIA member operators also take numerous steps in onboard water management. Water management techniques include:

- a. Use of technical water (for example: air conditioning condensate) where possible.
- b. Use of water recovery systems (for example: filtering and reuse of laundry water – last rinse use for first wash).
- c. Reclamation and reuse as technical water (flushing toilets, laundry, open deck washing) of properly treated and filtered wastewaters.
- d. Active water conservation (for example: use of reduced flow showerheads, vacuum systems for toilets, vacuum food waste transportation and laundry equipment that utilizes less water).

N. Graywater: *For ships traveling regularly on itineraries beyond the territorial waters of coastal states, CLIA member lines have agreed to discharge graywater only while the ship is underway and proceeding at a speed of not less than 6 knots¹; that graywater will not be discharged in port and will not be discharged within 4 nautical miles from shore or such other distance as agreed to with authorities having jurisdiction or provided for by local law except in an emergency, or where geographically limited. The member lines*

have further agreed that the discharge of graywater will comply with all applicable laws and regulations. For vessels whose itineraries are fully within US territorial waters, discharge shall comply fully with U.S. and individual state legislation and regulations.

The term graywater is used on ships to refer to wastewater that is generally incidental to the operation of the ship. The International Maritime Organization (IMO) defines graywater as including drainage from dishwasher, shower, laundry, bath and washbasin drains. The US Clean Water Act (formally know as the Federal Water Pollution Control Act) includes galley, bath and shower water in its definition of graywater. The US regulations implementing this act do not include a further definition of gray water. However, the regulations do include a provision that exempts all of the wastewater included in the IMO definition and other discharges incidental to the operation of a ship from the Clean Water Act's permitting program (formally known as the National Pollution Discharge Elimination System (NPDES) program). Finally, the US Coast Guard regulations include provisions that essentially combine the two definitions from the IMO and the Clean Water Act. None of the definitions of graywater include blackwater (discussed below) or bilgewater from the machinery spaces. Recent U.S. Legislation places limits on the discharge of graywater in the Alaska Alexander Archipelago.

Handling Method Employed by Member Lines:

Graywater is discharged only while ships are underway and proceeding at a speed of not less than 6 knots, in recognition that dispersal of these discharges is desirable and that mixing of these waters, which are discharged approximately 10-14 feet below the surface, by the action of the propellers and the movement of the ship, provides the best dispersal available.

- O. Blackwater:** *Waste from toilets, urinals, medical sinks and other similar facilities is called "blackwater." CLIA members have agreed that all blackwater will be processed through a Marine Sanitation Device (MSD), certified in accordance with U.S. or international regulations, prior to discharge. For ships traveling regularly on itineraries beyond the territorial water of coastal states, discharge will take place only when the ship is more than 4 miles from shore and when the ship is traveling at a speed of not less than 6 knots.¹*

For vessels whose itineraries are fully within US territorial waters, discharge shall comply fully with U.S. and individual state legislation and regulations.

P. Advanced Wastewater Purification Systems:

To improve environmental performance, cruise lines are testing and installing wastewater purification systems that utilize advanced technologies. These onboard wastewater treatment systems are designed to result in effluent discharges that are of a high quality and purity; for example, meeting or surpassing standards for secondary and tertiary effluents and reclaimed water. Effluents meeting these high standards would not be subjected to the strict discharge limitations previously discussed.

¹ For vessels operating under sail, or a combination of sail and motor propulsion, the speed shall not be less than 4 knots.

Q. Training and Educational Materials

Training is an important and ongoing part of every position and tasking onboard cruise ships. Not only is training necessary for the safe and economical operation of a ship, it is required by numerous international conventions and flag state regulations. The International Convention on Standards of Training Certification and Watchkeeping (STCW) for example, sets forth requirements for knowledge, experience and demonstrated competency for licensed officers of the deck and engineering departments and for ratings forming part of the navigation or engineering watch. Equivalent national standards apply to ships in United States registry. These detailed requirements address not only the navigation of the ship but also the proper operation of the shipboard machinery and knowledge of and ability to assure compliance with the environmental protection requirements of MARPOL and the safety regulations of The International Convention on Safety of Life at Sea (SOLAS). SOLAS also requires that the ship's training manual (which contents are prescribed by regulation) be placed in the crew messes and recreation rooms or in individual crew cabins.

CLIA member lines have developed programs that raise the level of environmental awareness on the part of both the passengers and the crew. Each ship's crew receives training regarding shipboard safety and environmental procedures. Advanced training in shipboard safety and environmental management procedures is provided for those directly involved in these areas. Those directly responsible for processing wastes are given specific instruction in their duties and responsibilities and in the operation of the various equipment and waste management systems. Specific actions that our member lines have taken to train employees and increase passenger awareness include:

- a. Announcements over the public address system and notices in ship newsletters that caution against throwing any trash overboard,
- b. Signage and colorful posters placed in crew and passenger areas encouraging environmental awareness and protection,
- c. Safety and environmental information booklets in crew cabins and crew lounges,
- d. Regular meetings of ship safety and environmental committees consisting of officers and crew from all departments to review methods of improving performance, including better and more effective environmental practices.

For ships on an international voyage, STCW, SOLAS, the International Management Code for the Safe Operation of Ships and for Pollution Prevention (ISM Code), require that training be fully documented. Individual training is documented in each crewmember's file. Ship training exercises, such as fire drills and emergency response exercises, are documented in the appropriate ship's logs. All of these training documents are required to be available for oversight examination by both the ship's flag state inspectors and by port state authorities such as the United States Coast Guard.

Placards warning of the prohibition of the discharge of oil are posted on all ships operating in the navigable waters of the United States as required by U.S. Coast Guard regulations (33CFR155.450). Additionally, as part of required shipboard waste management plans, both Coast Guard regulations (33CFR151.59) and MARPOL (Annex V Regulation 9) require the posting of placards that notify the passengers and the crew of the disposal requirements for garbage. These placards are to be written in the official language of the State whose flag the ship is entitled to fly and also in English or French if neither of these is the official

language. Once again, oversight of compliance with these requirements is conducted by ISM audits and frequent inspections by flag states and the United States Coast Guard.

For those ships on an international voyage, the Safety of Life at Sea Convention mandates compliance with the ISM Code. This comprehensive Code requires that each vessel operating company and each vessel participate in a very strictly defined management program, under both internal and external audit and regulatory oversight that sets forth detailed procedures for assuring compliance with safety, environmental protection, emergency response and training mandates.

Equivalent equipment, practices and procedures

CLIA member lines have agreed that the use of equivalent or other acceptable practices and procedures shall be communicated to CLIA. As appropriate, such practices and procedures shall be included as a revision to this document. As an example, when improved systems for treating blackwater and graywater are perfected, shown to meet the requirements for MSDs and accepted by appropriate authorities for the treatment of graywater, the new systems and associated technology will be included together with their impact on the current standard of discharging graywater only while underway.